

RCCBs RX³

residual current circuit breakers from 25 A to 63 A - AC and A types



Dimensions **see e-catalogue**

Conform to IEC 61008-1

- AC type : detect AC component faults
 - A type : detect AC and DC component faults
- Compatible with prong-type and fork type supply busbars
Do not accept auxiliaries

Pack	Cat.Nos	2-pole - 230 V \sim		
		AC type		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 24	30	25	2
1	4 020 25	30	40	2
1	4 020 26	30	63	2
1	4 020 27	30	80	2
1	4 020 28	100	25	2
1	4 020 29	100	40	2
1	4 020 30	100	63	2
1	4 020 32	300	25	2
1	4 020 33	300	40	2
1	4 020 34	300	63	2
		A type		
1	4 020 36	30	25	2
1	4 020 37	30	40	2
1	4 020 38	30	63	2

4-pole - 400 V \sim neutral on right-hand side

		AC type		
		Sensitivity (mA)	In (A)	Number of modules
1	4 020 62	30	25	4
1	4 020 63	30	40	4
1	4 020 64	30	63	4
1	4 020 66	100	25	4
1	4 020 67	100	40	4
1	4 020 68	100	63	4
1	4 020 70	300	25	4
1	4 020 71	300	40	4
1	4 020 72	300	63	4
		A type		
1	4 020 74	30	25	4
1	4 020 75	30	40	4
1	4 020 76	30	63	4

MCBs RX³ 3000

thermal magnetic MCBs from 6 A to 32 A - C curve



Technical characteristics **see e-catalogue**

Conform to IEC 60898-1

- Do not accept auxiliaries, and RCD add-on modules
 - Compatible with prong-type supply busbars
- Breaking capacity:
3000 - IEC 60898-1 - 230 V \sim

Pack	Cat.Nos	Single pole + neutral 230 V \sim neutral on left-hand side	
		C curve	
		Nominal rating In (A)	Number of modules
10	4 194 96	6	1
10	4 194 97	10	1
10	4 194 99	16	1
10	4 195 00	20	1
10	4 195 01	25	1
10	4 195 02	32	1

